



上海捷瑞德半导体  
Jerrett Semiconductor

JRP04N08

MOSFET

## 1. Description

JRP04N08, the N-channel Enhanced Power MOSFETs, is obtained by advanced double trench technology which reduce the conduction loss, improve switching performance and enhance the avalanche energy. This is suitable device for BMS and high current switching applications.

### KEY CHARACTERISTICS


Parameter	Value	Unit
$V_{DSS}$	85	V
$I_D$	120	A
$R_{DS(on).typ}$	3	$m\Omega$

### FEATURES

- Fast Switching
- Low On-Resistance ( $R_{DS(on)} \leq 3.6m\Omega$ )
- Low Gate Charge
- Low Reverse transfer capacitances
- High avalanche ruggedness
- RoHS product


### APPLICATIONS

- BMS
- Motor drivers



## ORDERING INFORMATION

Ordering Codes	Package	Product Code	Packing
JRP04N08-B	TO-263	P04N08	Reel
JRP04N08-P	TO-220	P04N08	Tube





上海捷瑞德半导体  
Jerrett Semiconductor

**JRP04N08**

MOSFET

## 2. ABSOLUTE RATINGS

at  $T_C=25^\circ\text{C}$ , unless otherwise specified

Symbol	Parameter	Rating	Units
$V_{DSS}$	Drain-Source Voltage	85	V
$I_D$	Continuous Drain Current, Silicon Limited	185	A
	Continuous Drain Current, Package Limited	120	A
	Continuous Drain Current @ $T_C=100^\circ\text{C}$ , Silicon Limited	117.2	A
$I_{DM}$ Note1	Pulsed Drain Current	480	A
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$E_{AS}$ Note2	Avalanche Energy	625	mJ
$P_D$	Power Dissipation	208.3	W
	Derating Factor above $25^\circ\text{C}$	1.67	W/ $^\circ\text{C}$
$T_J, T_{stg}$	Operating Junction and Storage Temperature Range	150, -55 to 150	$^\circ\text{C}$
$T_L$	Maximum Temperature for Soldering	260	$^\circ\text{C}$

Note1: Repetitive Rating: Pulse width limited by maximum junction temperature

Note2: L=0.5mH, Ias=50A, Start  $T_J=25^\circ\text{C}$

## 3. Thermal characteristics

Symbol	Parameter	Max	Units
$R_{\theta JC}$	thermal resistance, Junction-Case	0.6	$^\circ\text{C/W}$
$R_{\theta JA}$	thermal resistance, Junction-Ambient	62.5	$^\circ\text{C/W}$

## 4. Electrical Characteristics

at  $T_C=25^\circ\text{C}$ , unless otherwise specified

OFF Characteristics						
Symbol	Parameter	Test Conditions	Values			Units
			Min	Typ	Max	
$V_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS}=0\text{V}, I_D=250\mu\text{A}$	85	95	--	V
$I_{DSS}$	Drain-Source Leakage Current	$V_{DS}=85\text{V}, V_{GS}=0\text{V}$	--	--	1	$\mu\text{A}$
		$V_{DS}=68\text{V}, V_{GS}=0\text{V}$ $@T_C=125^\circ\text{C}$	--	--	100	$\mu\text{A}$
$I_{GSS(F)}$	Gate-Source Forward Leakage	$V_{GS}=+20\text{V}$	--	--	100	nA
$I_{GSS(R)}$	Gate-Source Reverse Leakage	$V_{GS}=-20\text{V}$	--	--	-100	nA



上海捷瑞德半导体  
Jerrett Semiconductor

**JRP04N08**

MOSFET

### ON Characteristics

Symbol	Parameter	Test Conditions	Values			Unit
			Min	Typ	Max	
$R_{DS(on)}$	Drain-Source On-Resistance	$V_{GS}=10V, I_D=50A$	--	3	3.6	$m\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu A$	2	3	4	V
Pulse width $t_p \leq 300\mu s, \delta \leq 2\%$						

### Dynamic Characteristics

Symbol	Parameter	Test Conditions	Values			Units
			Min	Typ	Max	
$C_{iss}$	Input Capacitance	$V_{DS}=42.5V, V_{GS}=0, f=1MHz$	--	6234	--	pF
$C_{oss}$	Output Capacitance		--	1181	--	
$C_{rss}$	Reverse Transfer Capacitance		--	97	--	
$Q_g$	Total Gate Charge	$V_{DD}=42.5V, I_D=50A, V_{GS}=10V$	--	124	--	nC
$Q_{gs}$	Gate-Source charge		--	31.2	--	
$Q_{gd}$	Gate-Drain charge		--	39.2	--	
$R_G$	Gate resistance	$V_{GS}=0, V_{DS}=0$		1.75		$\Omega$

### Switching Characteristics

Symbol	Parameter	Test Conditions	Values			Units
			Min	Typ	Max	
$t_{d(on)}$	Turn-On Delay Time	$V_{DD}=42.5V, I_D=10A, V_{GS}=10V, R_G=3\Omega, Resistive Load$	--	41	--	ns
$t_r$	Rise Time		--	68	--	
$t_{d(off)}$	Turn-Off Delay Time		--	76	--	
$t_f$	Fall Time		--	44	--	

### Source-Drain Diode Characteristics

Symbol	Parameter	Test Conditions	Values			Units
			Min	Typ	Max	
$I_s$	Continuous Source Current	$V_{GS}=0V, I_s=50A$	--	--	120	A
$I_{SM}$	Maximum Pulsed Current		--	--	480	A
$V_{SD}$	Diode Forward Voltage	$V_{GS}=0V, I_s=50A$	--	--	1.2	V
$T_{rr}$	Reverse Recovery Time	$I_s=30A, V_{GS}=0, di/dt=100A/us$	--	80	--	ns
$Q_{rr}$	Reverse Recovery Charge		--	112	--	nC



## 5. Characteristics Curves

Figure 1. Safe Operating Area




Figure 2. Maximum Power Dissipation vs Case Temperature




Figure 3. Maximum Continuous Drain Current vs Case Temperature




Figure 4. Typical Output Characteristics






Figure 5. Transient Thermal Impedance




Figure 6. Typical Transfer Characteristics




Figure 7. Source-Drain Diode Forward Characteristics






Figure 8. Drain-Source On-Resistance vs Drain Current




Figure 9. Normalized On-Resistance vs Junction Temperature




Figure 10. Normalized Threshold Voltage vs Junction Temperature





Figure 11. Normalized Breakdown Voltage vs Junction Temperature







上海捷瑞德半导体  
Jerrett Semiconductor

**JRP04N08**  
MOSFET

**Figure 12. Capacitance Characteristics**



**Figure 13. Typical Gate Charge vs Gate-Source Voltage**





## 6. Test Circuit and Waveform

Figure 14. Resistive Switching Test Circuit




Figure 15. Resistive Switching Waveforms




Figure 16. Gate Charge Test Circuit





Figure 17. Gate Charge Waveforms





上海捷瑞德半导体  
Jerrett Semiconductor

JRP04N08  
MOSFET

Figure 18. Diode Reverse Recovery Test Circuit




Figure 19. Diode Reverse Recovery Waveform




Figure 20. Unclamped Inductive Switching Test Circuit






Figure 21. Unclamped Inductive Switching Waveform





## 7. Package Description


TO-263



Items	Values(mm)	
	MIN	MAX
A	9.80	10.40
B	8.90	9.50
B1	0	0.10
C	4.40	4.80
D	1.16	1.37
E	0.70	0.95
F	0.30	0.60
G	1.07	1.47
H	1.30	1.80
K	0.95	1.37
L1	14.50	16.50
L2	1.60	2.30
I	0	0.2
Q	0°	8°
R	0.4	0.4
N	2.39	2.69



TO-220



Items	Values(mm)	
	MIN	MAX
A	9.60	10.6
B	15.0	16.0
B1	8.90	9.50
C	4.30	4.80
C1	2.30	3.10
D	1.20	1.40
E	0.70	0.90
F	0.30	0.60
G	1.17	1.37
H	2.70	3.80
L	12.6	14.8
N	2.34	2.74
Q	2.40	3.00
ΦP	3.50	3.90



上海捷瑞德半导体  
Jerrett Semiconductor

**JRP04N08**  
**MOSFET**

**NOTE:**

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. Please do not exceed the absolute maximum ratings of the device when circuit designing.
2. When installing the heat sink, please pay attention to the torsional moment and the smoothness of the heat sink.
3. MOSFETs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
4. Shanghai Jerrett reserves the right to make changes in this specification sheet and is subject to change without prior notice.