

Description

JRS180R70, the silicon N-channel Enhanced MOSFETs, is obtained by advanced Super Junction technology which reduce the conduction loss, improve switching performance. The transistor is suitable device for SMPS, high speed switching and general purpose applications

FEATURES

- Fast Switching
- 100% avalanche tested
- Improved dv/dt capability


Product Summary

Parameter	Value	Unit
$V_{DS@T_j,max}$	750	V
I_D	23	A
$R_{DS(ON),Typ}@V_{GS}=10V$	0.15	Ω


APPLICATIONS

- High frequency switching mode power supply


100% DVDS Tested!
100% Avalanche Tested!




TO-220F




TO-220



TO-252



TO-251



Schematic Diagram

Ordering Information

Device	Device Package	Product Code	Packing
JRS180R70-P	TO-220	S180R70	Tube
JRS180R70-A	TO-220F	S180R70	Tube
JRS180R70-U	TO-251	S180R70	Tube
JRS180R70-D	TO-252	S180R70	Tape Reel
JRS180R70-B	TO-263	S180R70	Tape Reel

Absolute Maximum Ratings($T_C=25^{\circ}\text{C}$ unless otherwise noted)

Parameter	Symbol	Rating	Units
Drain-to-Source Voltage	V_{DSS}	700	V
Continuous Drain Current	I_D	23	A
Continuous Drain Current $T_C = 100^{\circ}\text{C}$		14.5	A
Pulsed Drain Current(Note1)	I_{DM}	69	A
Gate-to-Source Voltage	V_{GS}	± 30	V
Single Pulse Avalanche Energy(Note2)	E_{AS}	500	mJ
Peak Diode Recovery dv/dt (Note3)	dv/dt	15	V/ns
Power Dissipation TO-251\TO-252\TO-220\TO-263	PD	220	W
Derating Factor above 25°C		1.75	W/ $^{\circ}\text{C}$
Power Dissipation TO-220F	P_D	42	W
Derating Factor above 25°C		0.33	W/ $^{\circ}\text{C}$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	150, -55 to 150	$^{\circ}\text{C}$
Maximum Temperature for Soldering	T_L	300	$^{\circ}\text{C}$

Thermal characteristics

Thermal characteristics TO-251\TO-252\TO-220\TO-263

Parameter	Symbol	Rating	Units
Junction-to-Case	$R_{\theta JC}$	0.57	$^{\circ}\text{C}/\text{W}$
Junction-to-Ambient	$R_{\theta JA}$	62.5	$^{\circ}\text{C}/\text{W}$

Thermal characteristics TO-220F

Parameter	Symbol	Rating	Units
Junction-to-Case	$R_{\theta JC}$	3	$^{\circ}\text{C}/\text{W}$
Junction-to-Ambient	$R_{\theta JA}$	80	$^{\circ}\text{C}/\text{W}$

Electrical Characteristics (TC=25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Values			Units
			Min	Typ	Max	
OFF Characteristics						
Drain to Source Breakdown Voltage	V_{DSS}	$V_{GS}=0V, I_D=250\mu A$	700	-	-	V
Bvdss Temperature Coefficient	$\frac{\Delta B_{VDSS}}{\Delta T_J}$	$I_D=250\mu A$, Reference 25°C	-	0.7	-	V/°C
Drain to Source Leakage Current	I_{DSS}	$V_{DS} = 700V$, $V_{GS} = 0V$, $T_j = 25^\circ C$	-	-	1	μA
		$V_{DS} = 560V$, $V_{GS} = 0V$, $T_j = 125^\circ C$	-	-	100	μA
Gate to Source Forward Leakage	$I_{GSS(F)}$	$V_{GS} = +30V$	-	-	100	nA
Gate to Source Reverse Leakage	$I_{GSS(R)}$	$V_{GS} = -30V$	-	-	-100	nA
ON Characteristics						
Drain-to-Source OnResistance	$R_{DS(ON)}$	$V_{GS}=10V$, $I_D=9A$ (Note4)	-	0.15	0.18	Ω
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{DS}=V_{GS}$, $I_D= 250\mu A$ (Note4)	2.5	-	4.5	V
Dynamic Characteristics						
Gate resistance	R_g	$f = 1.0MHz$	-	3.3	-	Ω
Output Capacitance	C_{iss}	$V_{GS} = 0V$ $V_{DS} = 25V$ $f = 1.0MHz$	-	1860	-	PF
Input Capacitance	C_{oss}		-	990	-	
Reverse Transfer Capacitance	C_{rss}		-	45	-	

Switching Characteristics, at $T_J = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Test Conditions	Values			Units
			Min.	Typ.	Max.	
Turn-on Delay Time	$t_{d(on)}$	$I_D = 11\text{A}$ $V_{DD} = 400\text{V}$ $V_{GS} = 10\text{V}$ $R_G = 2\Omega$	-	13	-	ns
Rise Time	t_r		-	8	-	
Turn-Off Delay Time	$t_{d(off)}$		-	37	-	
Fall Time	t_f		-	8	-	
Total Gate Charge	Qg	$I_D = 11\text{A}$ $V_{DD} = 400\text{V}$ $V_{GS} = 10\text{V}$	-	43	-	nC
Gate to Source Charge	Qgs		-	10	-	
Gate to Drain ("Miller") Charge	Qgd		-	15	-	

Source-Drain Diode Characteristics

Parameter	Symbol	Test Conditions	Values			Units
			Min.	Typ.	Max.	
Continuous Source Current (Body Diode)	I_S	TC=25 °C	-	-	23	A
Maximum Pulsed Current (Body Diode)	I_{SM}		-	-	69	A
Diode Forward Voltage	V_{SD}	$I_S = 11\text{A}$, $V_{GS} = 0\text{V}$ (Note4)	-	-	1.2	V
Reverse Recovery Time	T_{rr}	$I_S = 11\text{A}$, $T_J = 25^\circ\text{C}$ $dI_F/dt = 100\text{A}/\mu\text{s}$, $V_{GS} = 0\text{V}$	-	383	-	ns
Reverse Recovery Charge	Q_{rr}		-	5362	-	nC
Reverse Recovery Current	I_{rrm}		-	28	-	A

Characteristics Curves




Figure 3a Max Thermal Impedance (No FullPAK)




Figure 3b Max Thermal Impedance (FullPAK)




Figure 4 Typical Output Characteristics




Figure 5 Typical Transfer Characteristics




Figure 6 Typical Drain to Source ON Resistance vs Drain Current




Figure 7 Typical Drain to Source on Resistance vs Junction Temperature




Figure 8 Typical Theshold Voltage vs Junction Temperature




Figure 9 Typical Breakdown Voltage vs Junction Temperature




Figure 10 Typical Theshold Voltage vs Junction Temperature





Figure 11 Typical Breakdown Voltage vs Junction Temperature



6. Test Circuit and Waveform

Figure 12 Gate Charge Test Circuit




Figure 13 Gate Charge Waveforms




Figure 14 Resistive Switching Test Circuit




Figure 15 Resistive Switching Waveforms




Figure 16 Diode Reverse Recovery Test Circuit




Figure 17 Diode Reverse Recovery Waveform




Figure 18 Unclamped Inductive Switching Test Circuit






Figure 19 Unclamped Inductive Switching Waveform




Package Description




Items	Values(mm)	
	MIN	MAX
A	9.60	10.4
B	15.4	16.2
B1	8.90	9.50
C	4.30	4.90
C1	2.10	3.00
D	2.40	3.00
E	0.60	1.00
F	0.30	0.60
G	1.12	1.42
H	3.40	3.80
	1.60	2.90
L	12.0	14.0
N	2.34	2.74
Q	3.15	3.55
ϕP	2.90	3.30

TO-220F Package




Items	Values(mm)	
	MIN	MAX
A	9.60	10.6
B	15.0	16.0
B1	8.90	9.50
C	4.30	4.80
C1	2.30	3.10
D	1.20	1.40
E	0.70	0.90
F	0.30	0.60
G	1.17	1.37
H	2.70	3.80
L	12.6	14.8
N	2.34	2.74
Q	2.40	3.00
Φ P	3.50	3.90

TO-220 Package



Items	Values(mm)	
	MIN	MAX
A	9.80	10.40
B	8.90	9.50
B1	0	0.10
C	4.40	4.80
D	1.16	1.37
E	0.70	0.95
F	0.30	0.60
G	1.07	1.47
H	1.30	1.80
K	0.95	1.37
L1	14.50	16.50
L2	1.60	2.30
I	0	0.2
Q	0°	8°
R	0.4	
N	2.39	2.69

TO-263 Package



Items	Values(mm)	
	MIN	MAX
A	9.80	10.40
B	8.90	9.50
C	4.30	4.80
D	1.15	1.40
E	0.70	0.91
F	0.28	0.55
G	1.07	1.47
H	3.37	3.77
I	2.50	2.90
K	0.90	1.40
L	12.7	14.7
N	2.35	2.70

TO-262 Package

NOTE:

1. Exceeding the maximum ratings of the device in performance may cause damage to the device, even the permanent failure, which may affect the dependability of the machine. Please do not exceed the absolute maximum ratings of the device when circuit designing.
2. When installing the heat sink, please pay attention to the torsional moment and the smoothness of the heat sink.
3. MOSFETs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.
4. Shanghai Jerrett reserves the right to make changes in this specification sheet and is subject to change without prior notice.