## Hand Valve



- \* Compatible with CFC, HCFC, HFC and HFO refrigerants and oils
- $^{\star}$  Forged brass body with full size openings for maximum flow and minimum pressure drop
- \* Thermally stable hand wheel for operation in wide temperature ranges
- \* Working temp.: -40°C to +130°C

| Model     | Conn. Size | Conn. Type                     |
|-----------|------------|--------------------------------|
| 型号        | 接口尺寸       | 接口类型                           |
| VAHV-1/4F | 1/4"       | flare to flare, with brass nut |
| VAHV-3/8F | 3/8"       | flare to flare, with brass nut |
| VAHV-1/2F | 1/2"       | flare to flare, with brass nut |
| VAHV-5/8F | 5/8"       | flare to flare, with brass nut |
| VAHV-3/4F | 3/4"       | flare to flare, with brass nut |
| VAHV-1/4S | 1/4"       | solder to solder               |
| VAHV-3/8S | 3/8"       | solder to solder               |
| VAHV-1/2S | 1/2"       | solder to solder               |
| VAHV-5/8S | 5/8"       | solder to solder               |
| VAHV-3/4S | 3/4"       | solder to solder               |

- \* 适用于所有 CFC、HCFC 和 HFC 制冷剂及冷冻油
- \* 锻造黄铜阀体,坚固耐用的同时实现最大流量和最小压降
- \* 耐热手柄适用于各类环境工况
- \* 工作温度: -40°C to +130°C