

Vibration Absorber Tube



- * Compatible with CFC, HCFC, HFC and HFO refrigerants and oils
- * Stainless steel ferrule and wire braid
- * Brazed joint copper tube ends
- * Working temp.: -40°C to +120°C

Model 型号	Conn. 接口	Oval length 总长	Max. Working Pressure 最大工作压力	Burst Pressure 爆破压力
VAT-3/8	3/8" ODF	210 mm	500 PSI	2400 PSI
VAT-1/2	1/2" ODF	230 mm	500 PSI	2400 PSI
VAT-5/8	5/8" ODF	250 mm	500 PSI	2400 PSI
VAT-3/4	3/4" ODF	260 mm	500 PSI	2400 PSI
VAT-7/8	7/8" ODF	300 mm	500 PSI	2400 PSI
VAT-11/8	1-1/8" ODF	330 mm	500 PSI	2400 PSI
VAT-13/8	1-3/8" ODF	400 mm	500 PSI	2400 PSI
VAT-15/8	1-5/8" ODF	400 mm	500 PSI	2400 PSI
VAT-21/8	2-1/8" ODF	520 mm	425 PSI	1920 PSI
VAT-25/8	2-5/8" ODF	620 mm	355 PSI	1560 PSI
VAT-31/8	3-1/8" ODF	684 mm	285 PSI	1130 PSI

- * 适用于所有 CFC、HCFC 和 HFC 制冷剂及冷冻油
- * 不锈钢管套及织网
- * 铜管焊接接口
- * 工作温度: -40°C to +120°C