



SPECIFICATIONS

Current Rating: 1Amps
 Insulator Resistance: 5000Megohms min.
 Dielectric Withstanding: AC 500v
 Operating Temperature: -40° ~ +105° c
 Contact Material: Brass
 Insulator Material: PA6T
 PLATING: GOLD FLASH
 UNSPECIFIED TOLERANCE: ±0.20
 Dimen Sions List

Contacts Per row	Dimensions		Contacts Per row	Dimensions	
	A	B		A	B
1	2.54	0	21	53.34	50.80
2	5.08	2.54	22	55.88	53.34
3	7.62	5.08	23	58.42	55.88
4	10.16	7.62	24	60.96	58.42
5	12.70	10.16	25	63.50	60.96
6	15.24	12.70	26	66.04	63.50
7	17.78	15.24	27	68.58	66.04
8	20.32	17.78	28	68.58	68.58
9	22.86	20.32	29	71.12	68.58
10	25.40	22.86	30	73.66	71.12
11	27.94	25.40	31	76.20	73.66
12	30.48	27.94	32	78.74	76.20
13	33.02	30.48	33	81.28	78.74
14	35.56	33.02	34	83.82	81.28
15	38.10	35.56	35	86.36	83.82
16	40.64	38.10	36	88.90	86.36
17	43.18	40.64	37	91.44	88.90
18	45.72	43.18	38	93.98	91.44
19	48.26	45.72	39	96.52	93.98
20	50.80	48.26	40	101.6	96.52

HUIKE 东莞市辉科电子有限公司
 Dongguan HuiKe Electronics Co., Ltd.

工程变更通知单 ECN (DCN) NO.	版本 REV	日期 DATE	说明 DESCRIPTION	改变 CHANGE	承认 APPRO.	Angle 30~	±2°	DRAW	绘图
	P0					10~30	±0.5	DESIGN	设计
						~10	±0.15	CHECK	校阅
						GENERAL TOLERANCE (UNLESS OTHERWISE NOTED)		APPRO.	承认
						SCALE	1:1	UNIT	mm
						DATE:		A4	2016-6-18