



深圳显暘光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd

# PRODUCTION SPECIFICATION OF LCD MODULE

**MODULE NO.: XY067BHW8683ANT**

<b>Customer Name:</b>			
<b>Customer Part Number:</b>			
<b>Approved By:</b>		<b>Date:</b>	

<b>Prepared By</b>	<b>Checked By</b>	<b>Approved By</b>

## . Revision Record

Date	Rev.No.	Page	Revision Items	Prepared
2023.Jun.29	V1.0	ALL	First issued	



深圳显暘光电科技有限公司  
Shenzhen Xianyang Optoelectronic Technology Co., Ltd

## Table of Contents

No.	Item	Page
1	General Specifications	
2	Outline Drawing	
3	Interface signals	
4	Absolute Maximum Ratings	
5	Electrical Specifications and Instruction Code	
6	Optical Characteristics	
7	Reliability Test Items and Criteria	
8	Quality Level	
9	Precautions for Use of LCD Modules	








## 1. General Specifications

Item	Contents	Unit	Note
LCD Type	TFT	-	
Display color	16M		1
Viewing Direction	ALL	O'clock	
Operating temperature	-20~+70	°C	
Storage temperature	-30~+80	°C	
Module size	66.6*181.0*4.6	mm	2
Active Area(W×H)	60.19*160.51	mm	
Number of Dots	480×RGB×1280	dots	
Power Supply Voltage	3.3	V	
Backlight	12-LEDs (white)	pcs	
Brightness(LCM)	520(TYP)	cd/m <sup>2</sup>	TYP
Data Transfer	MIPI	-	
LCM Connector Type	AFC30-S40FCC-00	0.5PITCH 40pin	
Driver IC	FL7707		

Note 1: Color tune is slightly changed by temperature and driving voltage.

Note 2: Without FPC and Solder.

## 2. Outline.Drawing

1		2		3		4		5		6		7		8																																																																	
深圳市显扬光电科技有限公司										DESIGN: (设计)		CHECKED: (检查)		APPROVED: (批准)		SPECIFICATION		规格		EDITION: (版本号)																																																											
Date: (日期)										2023.06.29		Page: (页数)		1/1		图纸视角: 		CUSTOMER'S CODE: (客户型号)		XY067BMW8683ANT		EDITION: (版本号)		01																																																							
正视图										侧视图										背视图																																																											
																																																																															
Luminance: 5200nits LED service life: 50,000 Hours										1. Unit:mm. 2.  Modification rev.number. 3. All radii without dimension R0.3mm. 4. All draft angles to be 1.5° 5. Unspecified tolerances is : ±0.20mm. 6. Driver IC: FL7707 7. Display Type: 6.86 TFT 8. Operating Temperature : -20° ~ +70° C 9. Storage Temperature : -30° ~ +80° C 10. Requirements on Environmental Protection: ROHS HSF										Backlit circuit diagram										<table><tr><td>标示</td><td>日期</td><td>更改内容</td><td>签署</td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td><td> </td></tr></table>										标示	日期	更改内容	签署																																				
标示	日期	更改内容	签署																																																																												
Customer Name: 客户名称										Approval Date: 承认日期										Approved By: 承认										Please Confirm This Drawing Or/Before 请 签 回 此 图																																																	

**3 Interface signals**

Pin No.	Symbol	Function
1	GND	Ground
2	D0P	MIPI Data lane0 input ( positive )
3	D0N	MIPI Data lane0 input (negative)
4	GND	Ground
5	D1P	MIPI Data lane1 input ( positive )
6	D1N	MIPI Data lane1 input(negative)
7	GND	Ground
8	CLKP	MIPI CLK input ( positive )
9	CLKN	MIPI CLK input (negative)
10	GND	Ground
11	D2P	MIPI Data lane2 input ( positive )
12	D2N	MIPI Data lane2 input (negative)
13	GND	Ground
14	D3P	MIPI Data lane3 input ( positive )
15	D3N	MIPI Data lane3 input (negative)
16-17	GND	Ground
18-19	VCC-1V8	IO Power Supply(1.65V~3.6V)
20	REFCLK/NC	NC
21	SDA/NC	NC
22	SCL/NC	NC
23	BIST/NC	NC
24	RSTB	global reset pin. Active low to enter reset state. suggest to connecting with an RC reset circuit for stability. Normally pull high.
25	STBYB	NC
26	AVDD/NC	NC
27	GND	Ground
28-29	K	Backlight LED Ground
30	GND	Ground
31	VGL/NC	NC
32-33	GND	Ground
34	VGH/NC	NC
35-36	A	Backlight LED Power
38-39	VDD-3V3	Power Supply(3.3~3.6V)
40	VCOM/NC	NC



#### 4. Absolute Maximum Ratings(Ta=25°C)

##### 4.1 Electrical Absolute Maximum Ratings.(Vss=0V ,Ta=25°C)

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Note
Power supply	VDD	Ta=25°C	-	3.3	-	V	
Gate On Power Supply Voltage	VGH		-	15	-	V	
Gate Off Power Supply Voltage	VGL		-	-11	-	V	

Notes:

1. If the module is above these absolute maximum ratings. It may become permanently damaged.

Using the module within the following electrical characteristic conditions are also exceeded, the

module will malfunction and cause poor reliability.

2.  $V_{CC} > V_{SS}$  must be maintained.

3. Please be sure users are grounded when handling LCD Module

##### 4.2 Environmental Absolute Maximum Ratings.

Item	Storage		Operating		Note
	MIN.	MAX.	MIN.	MAX.	
Ambient Temperature	-30°C	80°C	-20°C	70°C	1,2
Humidity	-	-	-	-	3

1. The response time will become lower when operated at low temperature.

2. Background color changes slightly depending on ambient temperature.

The phenomenon is reversible.

3. Ta≤60°C:85%RH MAX.

Ta>60°C:Absolute humidity must be lower than the humidity of 85%RH at 40°C.



## 5. Electrical Specifications and Instruction Code

### 5.1 Electrical characteristics(V<sub>SS</sub>=0V ,T<sub>a</sub>=25°C)

Parameter	Symbol	Condition	Min	Typ	Max	Unit	Note
Power supply	VDD	T <sub>a</sub> =25°C	-	3.3	3.6	V	
Power supply	IOVCC	T <sub>a</sub> =25°C	-	1.8	-	V	
Input voltage	'H'	V <sub>IH</sub>	V <sub>IOVCC</sub> =1.8V	0.8V <sub>IOVCC</sub>	-	V <sub>IOVCC</sub>	V
	'L'	V <sub>IL</sub>	V <sub>IOVCC</sub> =1.8V	0	-	0.2V <sub>IOVCC</sub>	V

Note:

1:When an optimum contrast is obtained in transmissive mode.

2: Tested in 1×1 chessboard pattern.

### 5.2 LED backlight specification(V<sub>SS</sub>=0V ,T<sub>a</sub>=25°C)


Item	Symbol	Condition	Min	Typ	Max	Unit	Note
Supply voltage	-	-	-	9.6	-	V	1
Supply current	I <sub>f</sub>	-	-	120	-	mA	2
Forward current	Normal	3-chip series x 4	-	-	-	mA	
	Dimming		-	-	-		
LED LIFE	-	-	-	20000	-	Hrs	

Note:

1: V<sub>LED</sub>=V<sub>LED</sub>(+)-V<sub>LED</sub>(-).

2:The current of LED is 20mA.

A LED drive in constant current mode is recommended.





## 6. Optical Characteristics

Item	Symbol	Condition	Min.	Typ.	Max.	Unit	Note
Brightness	Bp	$\theta=0^\circ$	460	520	-	cd/m <sup>2</sup>	1
Uniformity	$\angle Bp$	$\Phi=0^\circ$	75	80	-	%	1,2
Viewing Angle	3:00	$Cr \geq 10$	70	80	-	Deg	3
	6:00		70	80	-		
	9:00		70	80	-		
	12:00		70	80	-		
Contrast Ratio	Cr	$\theta=0^\circ$	1000	1500		-	4
Response Time	$T_r+T_f$	$\Phi=0^\circ$	25	35	-	ms	5
Color of CIE Coordinate	W	x	-0.03	0.292	+0.03	-	1,6
		y	-0.03	0.331	+0.03	-	
	R	x	-0.03	0.660	+0.03	-	
		y	-0.03	0.324	+0.03	-	
	G	x	-0.03	0.257	+0.03	-	
		y	-0.03	0.582	+0.03	-	
	B	x	-0.03	0.134	+0.03	-	
		y	-0.03	0.121	+0.03	-	
NTSC Ratio	S		-	70	-	%	

Note: The parameter is slightly changed by temperature, driving voltage and material

Note 1: The data are measured after LEDs are turned on for 5 minutes. LCM displays full white.

The brightness is the average value of 9 measured spots. Measurement equipment BM-7 ( $\Phi 7.5\text{mm}$ )

Measuring condition:

- Measuring surroundings: Dark room.
- Measuring temperature:  $T_a=25^\circ\text{C}$ .
- Adjust operating voltage to get optimum contrast at the center of the display.


Measured value at the center point of LCD panel after more than 5 minutes while backlight turning on.





深圳显暘光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd




Note 2: The luminance uniformity is calculated by using following formula.

$$\Delta Bp = Bp \text{ (Min.)} / Bp \text{ (Max.)} \times 100 \text{ (\%)}$$

$Bp \text{ (Max.)}$  = Maximum brightness in 9 measured spots

$Bp \text{ (Min.)}$  = Minimum brightness in 9 measured spots.




Note 3: The definition of viewing angle:

Refer to the graph below marked by  $\theta$  and  $\phi$




深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd



Note 4: Definition of contrast ratio.( Test LCD using DMS501)



$$\text{Contrast ratio}(Cr) = \frac{\text{Brightness of selected dots}}{\text{Brightness of non-selected dots}}$$


Note 5: Definition of Response time. (Test LCD using DMS501):

The output signals of photo detector are measured when the input signals are changed from "black" to "white"(falling time) and from "white" to "black"(rising time), respectively. The response time is defined as the time interval between the 10% and 90% of amplitudes. Refer to figure as below.




深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd



The definition of response time

Note 6: Definition of Color of CIE Coordinate and NTSC Ratio.




Color gamut:

$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$

Note 7: Definition of cross talk.

$$\text{Cross talk ratio}(\%) = \frac{|\text{pattern A Brightness} - \text{pattern B Brightness}|}{\text{pattern A Brightness}} \times 100$$



Electric volume value=3F+/-3Hex



## 7. Reliability Test Items and Criteria

No	Test Item	Test condition	Criterion
1	High Temperature Storage	80°C±2°C 96H Restore 2H at 25°C Power off	1. After testing, cosmetic and electrical defects should not happen. 2. Total current consumption should not be more than twice of initial value.
2	Low Temperature Storage	-30°C±2°C 96H Restore 2H at 25°C Power off	
3	High Temperature Operation	70°C±2°C 96H Restore 2H at 25°C Power on	
4	Low Temperature Operation	-20°C±2°C 96H Restore 4H at 25°C Power on	
5	High Temperature/Humidity Operation	60°C±2°C 90%RH 96H Power on	
6	Temperature Cycle	-30°C ←————→ 80°C 30min 5min 30min after 5 cycle, Restore 2H at 25°C Power off	
7	Vibration Test	10Hz~150Hz, 100m/s <sup>2</sup> , 120min	Not allowed cosmetic and electrical defects.
8	Shock Test	Half- sine wave, 300m/s <sup>2</sup> , 11ms	
9	ESD Test	Air discharge: +/-8KV, Contact discharge: +/-4KV	

Note: Operation: Supply 2.8V for logic system.

The inspection terms after reliability test, as below

ITEM	Inspection
Contrast	CR>50%
IDD	IDD<200%
Brightness	Brightness>60%
Color Tone	Color Tone+/-0,05



## 8 Quality level

As Quality department <<Product Cosmetic SPEC>>.

## 9. Precautions for Use of LCD Modules

### 9.1 Handling Precautions

9.1.1 The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.

9.1.2 If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.

9.1.3 Do not apply excessive force to the display surface or the adjoining areas since this may cause the color tone to vary.

9.1.4 The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.

9.1.5 If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:

— Isopropyl alcohol

— Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

— Water

— Ketone

— Aromatic solvents

9.1.6 Do not attempt to disassemble the LCD Module.

9.1.7 If the logic circuit power is off, do not apply the input signals.

9.1.8 To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.

a. Be sure to ground the body when handling the LCD Modules.



- b. Tools required for assembly, such as soldering irons, must be properly ground.
- c. To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.
- d. The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.

## 9.2 Storage precautions

9.2.1 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.

9.2.2 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:

Temperature :         $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$

Relatively humidity:  $\leq 80\%$

9.2.3 The LCD modules should be stored in the room without acid, alkali and harmful gas.

**9.3 The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.**