

PRODUCTION SPECIFICATION OF LCD MODULE

MODULE NO.: XY070BFW8639ANT

Customer Name:			
Customer Part Number:			
Approved By:		Date:	
Prepared By	Checked By		Approved By

Table of Contents

Rev	rision History	3
1	General Specifications	4
2	Pin Assignment	
3	Absolute Maximum Ratings	
4	Electrical Characteristics	
5	INTERFACE TIMING	8
	5.1 System Bus Read/Write Characteristics	8
	5.2 Power ON/OFF Timing	9
6	Optical Characteristics	
7	Environmental / Reliability Test	
8	Mechanical Drawing	15
9	Precautions For Use of LCD Modules	

Revision History

Rev	Issued Date	Description	Page	Editor
1.0	Jan. 03,2024	First release	All	

1 General Specifications

	Feature	Specifications
	LCD type	6.9 inch
	Resolution (H*V)	280(RGB) * 1424
	Technology Type	a-Si TFT
Display Spec.	Pixel Configuration	R.G.B. Vertical Stripe
	Display Mode	Normally Black
	Viewing Direction	All
	Gray Scale Inversion Direction	
	Outline Dimensions (W x H x T) (mm)	38.2(H) *181.47(V)*3.54(T)
	Active Area(mm)	33.6 (H)*170.88(V)
Mechanical	With /Without Touch screen	Without
Characteristics	Match Connector Type	0.5pitch 30 pin
	Backlight Type	White LED
	Weight (g)	TBD
	Interface	MIPI 4LINE
Electrical Characteristics	Number of color	16.7M
Onaracteristics	Driver IC	FL7707-G5-D

2 Pin Assignment

NO.	PIN NAME	Description
1	LEDA	LED anode
2	LEDK1	LED Cathode
3	LEDK2	LED Cathode
4	VCI	Power Supply 2.8V
5	IOVCC	Power Supply 1.8V-2.8V
6	RESET	LCM reset signals
7	TE	Tearing effect output
8	PWM	The PWM frequency output for LCD driver control.
9	GND	Ground
10	D0P	DSI-D0+ data signals
11	DON	DSI-D0- data signals
12	GND	Ground
13	D1P	DSI-D1+ data signals
14	D1N	DSI-D1- data signals
15	GND	Ground
16	CLKP	DSI-Clock+ signals
17	CLKN	DSI-Clock- signals
18	GND	Ground
19	D2P	DSI-D2+ data signals
20	D2N	DSI-D2- data signals
21	GND	Ground
22	D3P	DSI-D3+ data signals
23	D3N	DSI-D3- data signals
24	GND	Ground
25	TP_INT NC	Touch Interrupt Dummy
26	TP_SDA NC	Touch IIC Data signal Dummy
27	TP_SCL NC	Touch IIC Clock signal Dummy
28	TP_RESET NC	Touch Reset Signal Dummy
29	TP_VCI NC	Touch Power supply Dummy
30	TP_IOVCC NC	Touch Power supply Dummy

3 Absolute Maximum Ratings

GND=0V, Ta= 25°C

Item	Symbol	Value	Unit
Power supply voltage for logic	V _{DD}	2.5~3.3	V
Input voltage	Vin V _{DD} +0.3		V
Operating temperature	Topr -20 to 70		. C
Storage temperature	Tstg	-30 to 80	。 C

4 Electrical Characteristics

4.1 Driving TFT LCD Panel

GND=0V, Ta=25℃

Item	Symbol	Min	Туре	Max	Unit	Test condition
Operating voltage	V _{DD}	2.5	2.8	3.3	V	-
MIPI supply Voltage	IOVCC	1.65	1.8	3.3	V	
Supply current	І рр	-	-	30	mA	V _{DD} =2.8V,Ta=25。C
	ViH	0.8VDD	-	VDD	V	
Input voltage	VIL	0	-	0.2VDD	V	-
Input leakage current	lı.	-1.0	-	1.0	μΑ	VIN=VDD or Vss

Note: Voltage greater than above may damage the module.


All voltages are specified relative to VSS=0V.

4.2 Driving Backlight


Ta=25°C

Item	Symbol	Min	Тур	Max	Unit	Remark
Forward Current	l F		80	_	mA	
Forward Voltage	V _F	_	12.8	_	V	
Connection mode	Р		4S2P			
LED number	/		8		pcs	
LED life time		20000			hours	

Note1: Optical performance should be evaluated at Ta=25°C only .If LED is driven by high current, high ambient temperature & humidity condition. The life time of LED will be reduced. Operating life means brightness goes down to 50% initial brightness. Typical operating life time is estimated data.




4.3 Block Diagram



5 INTERFACE TIMING

5.1 DSI Interface Timing Characteristics.





Rising and falling time on clock and data channel

Signal	Item	Combal		11-14		
	item	Symbol	Min.	Тур.	Max.	Unit
DOL CD/	Double UI instantaneous	2xUinst	TBD	2	25	ns
DSI_CP/ DSI_CN	UI instantaneous	UINSTA UINSTB	TBD	-	12.5	ns
DP/DN	Data to clock setup time	Tos	0.15xUI			ps
DP/DN	Data to clock hold time	Трн	0.15xUI	*		ps
DSI_CP/	Differential rise time for clock	Tortclk	150	-	0.3UI	ps
DSI_CN	Differential fall time for clock	Toftclk	150	-	0.3UI	ps
DP/DN	Differential rise time for data	TORTDATA	150	-	0.3UI	ps
DEIDIN	Differential fall time for data	TOFTDATA	150	2	0.3UI	ps

DSI High Speed Mode Characteristics

5.2 Power ON/OFF Timing





Power OFF sequence

6 Optical Characteristics

Ta=25℃


Item	Symbol	Condition	Min	Тур	Max	Unit	Remark
	θТ			85	ı		
Miow Anglos	θВ	CD > 10		85	ı	Dograd	Note 2
View Angles	θL	CR≥10		85	-	Degree	Note 2
	θR			85	ı		
Contrast Ratio	CR	θ=0°	800	1000	ı	-	Note1 Note3
Dognongo Timo	Ton	25℃		- 25	35	ms	Note1
Response Time	Toff		-				Note4
Uniformity	U	-	-	-	ı	%	Note1 Note6
NTSC	-	-	63	68	ı	%	Note 5
Luminance	L		-	650	-	cd/m ²	Note1 Note7

Test Conditions: V_F =12.8V, I_F =80mA, the ambient temperature is 25 $^{\circ}$ C.

1. The test systems refer to Note 1 and Note 2.

Note 1: Definition of optical measurement system.

The optical characteristics should be measured in dark room. After 5 minutes operation, the optical properties are measured at the center point of the LCD screen. All input terminals LCD panel must be ground when measuring the center area of the panel.



Item	Photo detector	Field	
Contrast Ratio			
Luminance	SR-3A	1°	
Chromaticity	SK-SA	ı	
Lum Uniformity			
Response Time	BM-7A	2°	

Note 2: Definition of viewing angle range and measurement system. viewing angle is measured at the center point of the LCD by CONOSCOPE(ergo-80).




Fig. 1 Definition of viewing angle

Note 3: Definition of contrast ratio

Contrast ratio (CR) = Luminance measured when LCD is on the "White" state

Luminance measured when LCD is on the "Black" state


"White state ": The state is that the LCD should be driven by Vwhite.

"Black state": The state is that the LCD should be driven by Vblack.

Vwhite: To be determined Vblack: To be determined.

Note 4: Definition of Response time

The response time is defined as the LCD optical switching time interval between "White" state and "Black" state. Rise time (TON) is the time between photo detector output intensity changed from 90% to 10%. And fall time (TOFF) is the time between photo detector output intensity changed from 10% to 90%.



Note 5: Definition of color chromaticity (CIE1931) Color coordinates measured at center point of LCD.

Note 6: Definition of Luminance Uniformity

Active area is divided into 9 measuring areas (Refer Fig. 2). Every measuring point is placed at the center of each measuring area.

Luminance Uniformity (U) = Lmin/Lmax

L-----Active area length W----- Active area width




Fig. 2 Definition of uniformity

Lmax: The measured maximum luminance of all measurement position.

Lmin: The measured minimum luminance of all measurement position.

Note 7: Definition of Luminance:

Measure the luminance of white state at center point.


7 Environmental / Reliability Test

Condition	Time (hrs)	Assessment
80, C	120	
70。C	120	
-30。C	120	
-20° C	120	No abnormalities in functions
60。C/ 90%RH	120	and appearance
-20 _o C ← 25 _o C → 70 _o C (0.5 hour ← 5 min → 0.5 hour)	10cycles	
	80, C 70, C -30, C -20, C 60, C/ 90%RH -20, C ← 25, C → 70, C	80, C 120 70, C 120 -30, C 120 -20, C 120 60, C/ 90%RH 120 -20, C ← 25, C → 70, C 10cycles

Remark:

- 1. The test samples should be applied to only one test item.
- 2. Sample size for each test item is 1~10pcs.
- 3.In case of malfunction defect caused by ESD damage, if it would be recovered to normal state after resetting, it would be judged as a good part.

8 Mechanical Drawing



9 Precautions For Use of LCD Modules

- **9.1** Handling Precautions
- 9.1.1.1 The display panel is made of glass. Do not subject it to a mechanical shock by dropping it from a high place, etc.
- 9.1.1.2 If the display panel is damaged and the liquid crystal substance inside it leaks out, be sure not to get any in your mouth, if the substance comes into contact with your skin or clothes, promptly wash it off using soap and water.
- 9.1.1.3 Do not apply eXYessive force to the display surface or the adjoining areas since this may cause the color tone to vary.
- 9.1.1.4 The polarizer covering the display surface of the LCD module is soft and easily scratched. Handle this polarizer carefully.
- 9.1.1.5 If the display surface is contaminated, breathe on the surface and gently wipe it with a soft dry cloth. If still not completely clear, moisten cloth with one of the following solvents:
 - Isopropyl alcohol
 - Ethyl alcohol

Solvents other than those mentioned above may damage the polarizer. Especially, do not use the following:

- Water
- Ketone
- Aromatic solvents
- 9.1.1.6 Do not attempt to disassemble the LCD Module.
- 9.1.1.7 If the logic circuit power is off, do not apply the input signals.
- 9.1.1.8 To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.
- 9.1.1.9 Be sure to ground the body when handling the LCD Modules.
- 9.1.1.10 Tools required for assembly, such as soldering irons, must be properly ground.
- 9.1.1.11 To reduce the amount of static electricity generated, do not conduct assembly and other work under dry conditions.
- 9.1.1.12 The LCD Module is coated with a film to protect the display surface. Be care when peeling off this protective film since static electricity may be generated.
- 9.1.1.13 Storage precautions
- 9.1.1.14 When storing the LCD modules, avoid exposure to direct sunlight or to the light of fluorescent lamps.
- 9.1.1.15 The LCD modules should be stored under the storage temperature range. If the LCD modules will be stored for a long time, the recommend condition is:
- 9.1.1.16 The LCD modules should be stored in the room without acid, alkali and harmful gas.
- **9.2** Transportation Precautions

The LCD modules should be no falling and violent shocking during transportation, and also should avoid eXYessive press, water, damp and sunshine.