



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd

Project No. 项目编号	
Customer 客户名称	
Module No. 客户型号	XY032CSN002-A2
Product type 产品内容	Standard LCD Module TFT: 240 xRGBx320Dots 3.2”TFT LCD

客户确认Customer Approval

项目负责人Project Manager	
品质主管Director of Quality	
采购工程师Purchasing Engineer	



CONTENTS

	<u>Page No.</u>
1. DOCUMENT REVISION HISTORY	3
2. GENERAL DESCRIPTION	4
3. MECHANICAL SPECIFICATIONS	4
4. INTERFACE SIGNALS	5
5. ABSOLUTE MAXIMUM RATINGS	7
6. ELECTRICAL SPECIFICATIONS	7
7. OPTICAL CHARACTERISTICS	8
8. TIMING CHARACTERISTICS	10
9. RELIABILITY TEST ITEM	11
10. SUGGESTIONS FOR USING LCD MODULES	15
11. PACKING(REFERENCE ONLY)	16



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd

1. Document revision history :

DOCUMENT REVISION	DATE	DESCRIPTION	PREPARED BY	APPROVED BY
A	2020.09.10	First Release.		



2. General Description

- . 3.2”(diagonal), 240 x3 RGB x 320 dots, 262k colors, Transmissive, TFT LCD module.
- . Viewing Direction: 12o'clock.
- . **Driving IC: ST7789V**
- . SPI 4W
- . Logic voltage: 2.8V (typ.).
- . Without touch panel.

3. Mechanical Specifications

The mechanical detail is shown in Fig. 1 and summarized in Table 1 below.

Table 1

Parameter		Specifications	Unit
主屏 Color TFT 240xRGBx320	Outline dimensions	55.04 (W) x77.20(H) x 2.58 (D)	mm
	TP view area	---	mm
	TP active area	---	mm
	LCD active area	48.60(W) x 64.80(H)	mm
	Display format	240 x3 RGB x 320	dots
	Color configuration	RGB stripes	-
	Pixel pitch	0.2025 x 0.2025	um
Weight		TBD	grams



Figure 1: Outline Drawing






Table 2: Pin assignment

[illegible]



5. Absolute Maximum Ratings

5.1 Electrical Maximum Ratings – for IC Only

Table 3: Electrical Maximum Ratings – for IC

Parameter	Symbol	Min.	Max.	Unit	Note
Power supply voltage (VDD)	VDD	-0.3	+4.0	V	1
Power supply voltage (IOVCC)	IOVCC	-0.3	+3.6	V	1

Note:

1. IOVCC, VCI, GND must be maintained.

2. The modules may be destroyed if they are used beyond the absolute maximum ratings.

5.2 Environmental Condition

Table 4

Item	Operating temperature (Topr)		Storage temperature (Tstg) (Note 1)		Remark
	Min.	Max.	Min.	Max.	
Ambient temperature	-20. C	+70. C	-30. C	+80. C	Dry
Humidity (Note 1)	80% max. RH for Ta ≤ 40C < 50% RH for 40C < Ta ≤ Maximum operating temperature				No condensation

Note 1: Product cannot sustain at extreme storage conditions for long time.

6. Electrical Specifications

Typical Electrical Characteristics

At Ta = 25 . C, VCI = 2.6V to 3.3V, IOVCC = 1.65V to 3.3V GND = 0V.

Table 5

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Supply voltage (analog)	VCI-GND		2.6	2.8	3.3	V
Supply voltage (logic)	IOVDD-GND		1.65	1.8	3.3	V
Supply current (Logic & LCD)	ICC	VCI=2.8V	-	-	10	mA
Supply voltage of white LED backlight	VLED = V(BL+) - V(BL-)	Forward current = 100 mA	3.0	3.2	3.4	V
Luminance (on the module surface)		Number of LED dies = 5	-	260	-	cd/m ²



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd

7. Optical Characteristics

7.1 Optical specification

Item		Symbol	Condition	Min.	Typ.	Max.	Unit	Note	
Transmittance (without Polarizer)		T(%)	—	-	18.0	—	—		
Contrast Ratio		CR	$\Theta=0$	400	500	-	-	(1)(2)	
Response time	Rising	T _R	Normal viewing angle	-	4	8	msec	(1)(3)	
	Falling	T _F		-	-	12			24
				-	-				
Color gamut		S(%)			60		%		
Color chromaticity (CIE1931)	White	W _x		0.283	0.303	0.323		(1)(4) CF glass (C-light)	
		W _y		0.305	0.325	0.345			
	Red	R _x		0.606	0.626	0.646			
		R _y		0.314	0.334	0.354			
	Green	G _x		0.257	0.277	0.297			
		G _y		0.529	0.549	0.569			
	Blue	B _x		0.122	0.142	0.162			
		B _y		0.102	0.122	0.142			
Viewing angle	Hor.	Θ_L	CR>10	35	45	-			
		Θ_R		35	45	-			
	Ver.	Θ_U		35	50	-			
		Θ_D		10	20	-			
Optima View Direction		12 O'clock						(5)	

7.2 Measuring Condition

- Measuring surrounding : dark room
- Ambient temperature : $25\pm 2^\circ\text{C}$
- 15min. warm-up time.

7.3 Measuring Equipment


- FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics.



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd


Note (1) Definition of Viewing Angle : Θ_U




Note (2) Definition of Contrast Ratio(CR) :

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$

Note (3) Definition of Response Time : Sum of T_R and T_F



Note (4) Definition of optical measurement setup





8. Timing Characteristics

8.4.3 Serial Interface Characteristics (4-line serial):




Figure 5 4-line serial Interface Timing Characteristics

$V_{DDI}=1.65$ to $3.3V$, $V_{DD}=2.4$ to $3.3V$, $AGND=DGND=0V$, $T_a=-30$ to 70 °C

Signal	Symbol	Parameter	MIN	MAX	Unit	Description
CSX	T_{CSS}	Chip select setup time (write)	15		ns	
	T_{CSH}	Chip select hold time (write)	15		ns	
	T_{CSS}	Chip select setup time (read)	60		ns	
	T_{SCC}	Chip select hold time (read)	65		ns	
	T_{CHW}	Chip select "H" pulse width	40		ns	
SCL	T_{SCYCW}	Serial clock cycle (Write)	66		ns	- write command & data ram
	T_{SHW}	SCL "H" pulse width (Write)	15		ns	
	T_{SLW}	SCL "L" pulse width (Write)	15		ns	
	T_{SCYCR}	Serial clock cycle (Read)	150		ns	- read command & data ram
	T_{SHR}	SCL "H" pulse width (Read)	60		ns	
	T_{SLR}	SCL "L" pulse width (Read)	60		ns	
D/CX	T_{DCS}	D/CX setup time	10		ns	
	T_{DCH}	D/CX hold time	10		ns	
SDA (DIN)	T_{SDS}	Data setup time	10		ns	
	T_{SDH}	Data hold time	10		ns	
DOUT	T_{ACC}	Access time	10	50	ns	For maximum CL=30pF For minimum CL=8pF
	T_{OH}	Output disable time	15	50	ns	

Table 6 4-line serial Interface Characteristics

Note : The rising time and falling time (T_r , T_f) of input signal are specified at 15 ns or less. Logic high and low levels are specified as



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd

9. Reliability Test Item

Test Item	Sample Type	Test Condition	Test result determinant gist
High temperature storage	Normal temperature	70±3℃;96H	the inspection of appearance and function character.
	Wide temperature	80±3℃;96H	
Low temperature storage	Normal temperature	-20±3℃;120H	
	Wide temperature	-30±3℃;120H	
High temperature /humidity storage	Normal temperature	50℃±3℃,90%±3%RH;96H	
	Wide temperature	60℃±3℃,90%±3%RH;96H	
High temperature operation	Normal temperature	60±3℃;96H	no objection of the function character; no fatal objection of the appearance.
	Wide temperature	70±3℃;96H	
Low temperature operation	Normal temperature	0±3℃;96H	
	Wide temperature	-20±3℃;96H	
High temperature /humidity operation	Normal temperature	40℃±3℃,90%±3%RH;96H	
	Wide temperature	50℃±3℃,90%±3%RH;96H	
Temperature Shock	Normal temperature	-20±3℃,30min→70±3℃,30min;10cycle	inspect the objections appearance、function & the whole structure
	Wide temperature	-30±3℃,30min 80±3,30min;10cycle	The inspection of appearance、function & the whole structure

9.1 特殊检验要求:



检查项目	可接受标准	备注
背光	1. 无背光不接受	目视检查/放大镜
	2. 亮度, 均匀度及功耗须在 SPEC 之内	
	3. 颜色坐标需在规格内或依据限度	
	4. 非背光框变形的漏光在玻璃外缘可以接受	
铁壳	任何明显可见的损坏、变形和其它铁壳上有锡渣不可接受	
FPC	1. 变形和折痕标准如图所示, 两条折痕的角度不能超过90°	
	2. 补强板裂、破损、外来材料和气泡的面积, 如果超过补强板的1/5 不能接受	
	3. 金手指部位有明显划伤、污点和外来细小指针状的异物都不可接受	
	4. 金手指氧化或者电镀不良不可以接受	
	5. pad 脱落或者断裂不可接受	



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd


9.2 TFT&触摸屏检查标准如下表：

检查项目	Accessible standard			备注
	length (mm)	wide (mm)	Accessible QTY	
1. 线状缺陷(黑/白线等)		$W \leq 0.05$	access	
	$L \leq 5$	$0.05 < W \leq 0.1$	1	
2. 划伤		$W \leq 0.05$	access	
	$L \leq 5$	$0.05 < W \leq 0.1$	1	


3. 点状缺陷	size(mm)	Accessible QTY
	$D \leq 0.10$	access
	$0.10 < D \leq 0.20$	2
	$0.2 < D \leq 0.25$	1
	$D > 0.25$	0

$$D = (\text{长边直径 } X + \text{短边直径 } Y) / 2$$

4. TP 鱼眼、凹点、气泡	size(mm)	Accessible QTY
	$D \leq 0.20$	access
	$0.20 < D \leq 0.30$	6
	$0.3 < D \leq 0.5$	2
	$D > 0.5$	0



5. 牛顿环检查
- A 均匀牛顿环(图 A)
1. 如牛顿环面积大小超过 T/P 整个面积的1/4, 则不可接受.
 2. 在荧光灯下, 如牛顿环小于 T/P 的 1/4 且不影响显示字体效果, 则可接受



A



B



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd


不均匀牛顿环(图 B)

1. 在无荧光灯下, 如牛顿环大于 7mm, 则不可接受

2. 在莹光灯下, 无论大小只要造成文字失真或直

B


线变形, 判定 NG



备注: 檢驗時要撕起保護膜, 检查规格参照点状、線状异物混入判定标准。

以上的点缺陷距离必须大于 5mm &点、线缺陷相加后可接受数量之总和为 5

代号说明: X:崩裂长度 Y:崩裂宽度 Z:崩裂厚度 a:LCD 边长 D:端子长度 t:玻璃厚度



6. 表面及
中间崩裂

$$Z \leq 1/2t$$
$$Z \leq 1/2t$$

$$X \leq a$$
$$X \leq a$$


不可以进入 SP 内缘
需要保留 1/2 SP 宽度

7. 角落崩
裂


$$Z \leq 1/2t$$
$$Z \leq 1/2t$$

$$X \leq 1/8a$$
$$X \leq 1/8a$$

不可以进入 SP 内缘
需要保留 1/2 SP 宽度



8 电极端
子区崩裂



正面
背面

$$X \leq 1/5a$$
$$X \leq 1/5a$$

$$Y \leq 0.5mm$$
$$Y \leq 0.5mm$$

$$z \leq t$$
$$z \leq 1/2t$$

以上崩裂超过一处时间, X 是所有崩裂长度的总和; 正面的崩裂不可以进入视区。

每一单处电极的崩裂宽度不超过原电极宽度的 1/4

9. 裂

任何有延伸趋势的裂痕都不可接受

玻璃、反射片与偏光片的破损及划伤遵照点状缺陷和线状缺陷标准



Minor

偏光片、反
射片与玻
璃不良

不应有贴反、未贴、贴错等现象

尺寸应符合规范, 不应无保护膜

贴歪的偏光片应该显现全部的 SP 框形

Minor



深圳显昶光电科技有限公司

Shenzhen Xianyang Optoelectronic Technology Co., Ltd

缺行、缺列、串扰、乱码不可以接受

色度、灰度、亮度、均匀度和对比度失常（对比 Golden Sample 和 Spec.）

不显示的像素中异常点/线（工艺形成）遵照点状缺陷和线状缺陷标准

显示偏、斜（S）遵照下表：

有效可视 面不良（电 测）	$S < 0.3\text{mm}$	可接受	Major
	$0.3\text{mm} \leq S < 0.5\text{mm}$	缺陷级别Minor	
	$S \geq 0.5\text{mm}$	缺陷级别Major	

在批处理中如果有两种或两种以上的偏/斜同时存在，遵照最高缺陷级别
表面上不能有软布轻擦不去或气枪吹不干净的异物（包括布丝、灰尘、
焊锡球、粘胶、阴影等）依据点线规格判定

条彩，错开，流迹，玻璃漏光依据彩色画面判定

视角错误不可以接受；显示看见水波纹不可以接受；抖面 不可以接受

漏失	1. 视区内发现不规则状黑团，亮团（挤压玻璃会移动）不可以接受	Major
	2. 空穴回弹：敲击气泡不可以接受	

COG 区	1. IC 处不可有破损、划伤	minor
	2. 封口胶进入视区不可以接受，	
	3. 封口胶脱落，如果渗胶深度达到要求，可以接受。	
	4. 表面的涂布胶位置依据作业文件要求，高度不可以超过上偏光片，必须 完全覆盖端子的 ITO 线路	

如果上述不良不发生在可视区域, 标准可以适当放松

9.3 TFT 特别检查：

检查项目	可接受标准	图表
像素缺陷 的定义	像素/3 个元素(R+G+B)	
	点/1 个元素(R/G/B)	

亮点：与周围邻近 pixel 对比较亮的点为亮点，超过一个 sub pixel 面
积的 1/2时计为一个亮点. 颜色有红、绿、蓝三种, 亮点可在 R、G、B 三
个画面中的两个画面可视，在全白画面不可视；

暗点：与周围邻近 pixel 对比较暗的点为暗点，超过一个 sub pixel 面
积的 1/2 时计为一个暗点. 颜色为暗黑色，暗点在 R、G、B 三个画面中
的一个画面可视，在全白画面可视；

相邻点的定义: 2 个或 3 个点连续元素点(R+G/G+B/B+R/R+G+B).

		可接受判定标准	
		失效模式	数量
点缺陷判 定标准	目视/测量卡	亮点	点的形式
			任何(红, 蓝, 绿)
			2 个连接点
			暗点
		暗点	
			2 个连接点
			>=3 个相邻的点



10. Suggestions for using LCD modules

10.1 Handling of LCM

1. The LCD screen is made of glass. Don't give excessive external shock, or drop from a high place.
2. If the LCD screen is damaged and the liquid crystal leaks out, do not lick and swallow. When the liquid is attach to your hand, skin, cloth etc, washit off by using soap and water thoroughly and immediately.
3. Don't apply excessive force on the surface of the LCM.
4. If the surface is contaminated ,clean it with soft cloth. If the LCM is severely contaminated , use Isopropyl alcohol/Ethyl alcohol to clean. Other solvents may damage the polarizer . The following solvents is especially prohibited: water , ketone Aromatic solvents etc.
5. Exercise care to minimize corrosion of the electrode. Corrosion of the electrodes is accelerated by water droplets, moisture condensation or a current flow in a high-humidity environment.
6. Install the LCD Module by using the mounting holes. When mounting the LCD module make sure it is free of twisting, warping and distortion. In particular, do not forcibly pull or bend the I/O cable or the backlight cable.
7. Don't disassemble the LCM.
8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.
 - Be sure to ground the body when handling the LCD modules.
 - Tools required for assembling, such as soldering irons, must be properly grounded.
 - To reduce the amount of static electricity generated, do not conduct assembling and other work under dry conditions.
 - The LCD module is coated with a film to protect the display surface. Exercise care when peeling off this protective film since static electricity may be generated.
9. Do not alter, modify or change the the shape of the tab on the metal frame.
10. Do not make extra holes on the printed circuit board, modify its shape or change the positions of components to be attached.
11. Do not damage or modify the pattern writing on the printed circuit board.
12. Absolutely do not modify the zebra rubber strip (conductive rubber) or heat seal connector
13. Except for soldering the interface, do not make any alterations or modifications with a soldering iron.
14. Do not drop, bend or twist LCM.


10.2 Storage

1. Store in an ambient temperature of 5 to 45 C, and in a relative humidity of 40% to 60%. Don't expose to sunlight or fluorescent light.
2. Storage in a clean environment, free from dust, active gas, and solvent.
3. Store in antistatic container.



11. Packing (Reference only)

Packing Method



1. Put module into tray cavity :
2. Tray stacking
3. Put 1 cardboard under the tray stack and 1 cardboard above:
4. Fix the cardboard to the tray stack with adhesive tape:
5. Put the tray stack into carton.
6. Carton sealing with adhesive tape.

- END -