



GV101WXB-NN0-3GP0

TFT- LCD

REV. P0

ISSUE DATE

2019-10-18

PAGE


1 OF 23


XY101WXB-NN0-5

BUYER	
SUPPLIER	
FG-Code	

ITEM SIGNATURE	BUYER DATE
_____	_____
_____	_____
_____	_____

ITEM DATE	SUPPLIER SIGNATURE
Prepared	_____
Reviewed	_____
Approved	_____

深圳显昶光电科技有限公司		REV	ISSUE DATE	
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18	
GV101WXB-NN0-3GP0		XY101WXB-NN0Product Specification		PAGE 2 OF 23
REVISION HISTORY				
REV.	ECN No.	DESCRIPTION OF CHANGES	DATE	PREPARED
P0		Initial Release	2019-10-18	

深圳显昶光电科技有限公司		REV	ISSUE DATE	
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18	
GV101WXB-NN0-3GP0	XY101WXB-NN0Product Specification			PAGE 3 OF 23


Contents

No.	Items	Page
1.0	General Description	4
2.0	Absolute Maximum Ratings	6
3.0	Electrical Specifications	7
4.0	Optical Specifications	12
5.0	Reliability Test	15
6.0	Packing Information	16
7.0	Product Label	18
8.0	Handling & Cautions	19
9.0	Appendix	22

1.1 GENERAL DESCRIPTION

1.2 Introduction

XY101WXB-NN0 - 5 is a color active matrix TFT LCD FOB using amorphous silicon TFT 's (Thin Film Transistors) as an active switching devices. This module has a 10.1 inch diagonally measured active area with WXGA resolutions (1280 horizontal by 800 vertical pixel array). Each pixel is divided into RED, GREEN, BLUE dots which are arranged in vertical stripe and this module can display 16.7M colors.



1.3 Features

- LVDS Interface;
- 6bit + Hi-FRC display 16.7M colors
- High contrast ratio and Transmittance

2.1 ABSOLUTE MAXIMUM RATINGS


The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit.

< Table 2. Absolute Maximum Ratings >

Parameter		Symbol	Min.	Max.	Unit	Remarks
Power Supply	LCD Module	VDD	VSS-0.3	3.6	V	Ta = 25 °C Note 1&2
Operating Temperature		T _{OP}	-20	+70	°C	Note 3
Storage Temperature		T _{ST}	-30	+80	°C	
Operating Ambient Humidity		H _{OP}	10	90	%RH	
Storage Humidity		H _{st}	10	90	%RH	

Note:

- These range above is maximum value not the actual operating temperature . Actual Operating temperature is no more than 40°C and temperature refers to the LCM surface temperature ; Length of operation: No more than 8 hours per day, and no more than 4 hours of continuous use one time.
- BOE is not responsible for product problems beyond the use conditions.
- Temperature and relative humidity range are shown in the figure below. Wet bulb temperature should be 39 °C max. and no condensation of water.



3.1 ELECTRICAL SPECIFICATIONS

3.2 TFT LCD Module



< Table 3. LCD Module Electrical specifications > [Ta =25±2 °C]

Parameter	Symbol	Values			Unit	Notes
		Min.	Typ.	Max.		
Power Supply Voltage	VDD	3.0	3.3	3.6	V	
	VRP			300	mV	Ripple
Power Supply Current	IDD	—	212	364	mA	Note 1
Power Consumption	PLCD	—	0.7	1.2	W	
Rush current	IRUSH	—	—	3.0	A	Note 2
CMOS Interface	Input Voltage	VIH	2.7		V	
		VIL	0		V	
	Output Voltage	VOH	2.7		V	
		VOL	0		V	

Notes : 1. The supply voltage is measured and connector of LCM.

The current draw and power consumption VDD=3.3V, Frame rate $f_v=60\text{Hz}$ and Clock 72.4MHz. Test Pattern of power supply

- a) Typ : Mosaic 8 x 6 Pattern(L0/L25)
b) Max : skip subPixel(L255)



2. The duration of rush current is about 2ms and rising time of Power Input is 1ms(min) **R2015-6014-A**

3.2 INPUT TERMINAL PIN ASSIGNMENT


This LCD employs one interface connections, a 40 pin connector is used for the LCD module electronics interface.

3.2.1 Pin assignment for LCD module

Connector : **MSAK24025P40G** (STM) or equivalent

< Table4. Pin Assignment for LCD Module Connector >


Pin No.	Symbol	Description	I/O
1	NC	Non Connection	—
2	VDDIN	Power supply VDDIN=3.3V (Typ.)	P
3	VDDIN		P
4	VDDIN		P
5	NC	Non Connection	—
6	GND	GROUND	P
7	GND	GROUND	P
8	RIN0-	LVDS Negative data signal (-)	I
9	RIN0+	LVDS Positive data signal (+)	I
10	GND	GROUND	P
11	RIN1-	LVDS Negative data signal (-)	I
12	RIN1+	LVDS Positive data signal (+)	I
13	GND	GROUND	P
14	RIN2-	LVDS Negative data signal (-)	I
15	RIN2+	LVDS Positive data signal (+)	I
16	GND	GROUND	P
17	LVDS_CLK-	LVDS Negative CLK signal (-)	I
18	LVDS_CLK+	LVDS Positive CLK signal (+)	I
19	GND	GROUND	P
20	RIN3-	LVDS Negative data signal (-)	I


深圳显昶光电科技有限公司		REV	ISSUE DATE		
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18		
GV101WXB-NN0-3GP0	XY101WXB-NN0Product Specification				PAGE 10 OF 23

3.3 Interface timing Parameter


< Table5. LVDS Timing Parameter >

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
DCLK Frequency	Fdclk	66.3	72.4	78.9	MHz
Horizontal display area	Thd	1280			pixel
HSYNC period time	Th	1380	1440	1500	pixel
HSYNC blanking	thbp+ thfp	100	160	220	pixel
Vertical display area	Tvd	800			H
Frequency	fV	55	60	65	Hz
VSYNC period time	Tv	824	838	872	H
VSYNC blanking	Tvbp+ Tvfp	24	38	72	H




深圳显昶光电科技有限公司		REV	ISSUE DATE	
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18	
GV101WXB-NN0-3GP0	XY101WXB-NN0Product Specification			PAGE 11 OF 23

3.4 Power Sequence




< Table6. Sequence Table >

Parameter	Values			Units
	Min	Typ	Max	
T1 — ms			10	0
T2	0	—	50	ms
T3	200	—	—	ms
T4	500	—	—	ms
T5	0	—	50	ms
T6	0	—	10	ms
T7	500	—	—	ms

深圳显昶光电科技有限公司		REV	ISSUE DATE	
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18	
GV101WXB-NN0-3GP0	XY101WXB-NN0Product Specification			PAGE 13 OF 23

Note 1:The definition of Viewing Angle
Refer to the graph below marked by θ and Φ .




Note2:The definition of Contrast Ratio

Contrast Ratio(CR)= $\frac{\text{Luminance When LCD is at "White" state}}{\text{Luminance When LCD is at "Black" state}}$

(Contrast Ratio is measured in optimum common electrode voltage)


Note3:Definition of Response time.(Test LCD using RD80S or similar equipments):
The output sign also photo detector are measured when the input sign also are changed from "black " to "white" (Voltage falling time)and from "white" to "black" (Voltage rising time), respectively . The response time is defined as the time interval between the 10% and 90% of amplitudes . Refer to figures below.



Note 4: Color Coordinates of CIE 1931
The test condition is at ILED=20mA and measured on the surface of LCD module at 25°C.
Measurement equipment:CS2000 or similar equipments
The Color Coordinate (CIE 1931) is the measurement of the center of the display shown in below figure.

Note 5: Definition of Color of CIE Coordinate and NTSC Ratio.


$$S = \frac{\text{area of RGB triangle}}{\text{area of NTSC triangle}} \times 100\%$$

**Note 6: gamma curve control**

- For gamma curve control, HUAWEI's request
- 1, the whole curve's tolerance must control within ± 0.3 , HUAWEI will test the gray scale below: 0, 8, 16, 25, 33, 41, 49, 58, 66, 74, 82, 90, 99, 107, 115, 123, 132, 140, 148, 156, 165, 173, 181, 189, 197, 206, 214, 222, 230, 239, 247, 255

Note 7: Polarization Direction Definition


- Viewing direction is normal user viewing direction which is vertical to the display surface
- The polarizer which is closer to viewer is defined as Front Polarizer
- The polarizer which is on the rear side of viewer is defined as Rear Polarizer
- The X axis is defined as parallel line to top & bottom sidelines of the Active Area
- PdF which is marked in blue arrow is polarization degree of Front polarizer
- PdR which is marked in red arrow is polarization degree of Back polarizer
- The polarization degree of Back polarizer be indicated in range of 0deg to 180deg according to the definition



6.0 PACKING INFORMATION(产品形态：FOB)


5. Packing procedure:

- 将 1pcs FOB 平放入 Tray,
上下 EPE 垫片
CF 侧向上放置;




Tray


- 将 26pcs PET Tray 平放入
Shielding Bag
进行抽真空处理;
- Tray 无需区分旋转码放



- 每个 Pallet 上放 3 层 Box,
1 层 4 箱
- Pallet 缠绕膜包装
- 600pcs / Pallet




- 将 PET Tray 堆码后平放入 Inner Box
上下放置 EPE Board
- 容量：50pcs/Inner Box



6.1 Packing Note(产品形态：FOG)

- . Box Dimension: 500mm(W) x
400mm(D) x 290mm(H) . Package
Quantity in one Box: 25pcs

深圳显昶光电科技有限公司		REV	ISSUE DATE	
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18	
GV101WXB-NN0-3GP0	XY101WXB-NN0Product Specification			PAGE 16 OF 23


8.1 Handling & Cautions

8.2 Mounting Method

- The panel of the LCD consists of two thin glasses with polarizers which easily get damaged. So extreme care should be taken when handling the LCD.
- Excessive stress or pressure on the glass of the LCD should be avoided. Care must be taken to insure that no torsional or compressive forces are applied to the LCD unit when it is mounted.
- If the customer's set presses the main parts of the LCD, the LCD may show the abnormal display. But this phenomenon does not mean the malfunction of the LCD and should be pressed by the way of mutual agreement.
- To determine the optimum mounting angle, refer to the viewing angle range in the specification for each model.
- Mount a LCD module with the specified mounting parts.

8.2 Caution of LCD Handling and Cleaning

- Since the LCD is made of glass, do not apply strong mechanical impact or static load onto it. Handling with care since shock, vibration, and careless handling may seriously affect the product. If it falls from a high place or receives a strong shock, the glass may be broken.
- The polarizers on the surface of panel are made from organic substances. Be very careful for chemicals not to touch the polarizers or it leads the polarizers to be deteriorated.
- If the use of a chemical is unavoidable, use soft cloth with solvent (recommended below) to clean the LCD 's surface with wipe lightly.
-IPA(Isopropyl Alcohol), Ethyl Alcohol, Trichlorotrifluoroethane
- Do not wipe the LCD's surface with dry or hard materials that will damage the polarizers and others. Do not use the following solvent.
-Water, Ketone, Aromatics
- It is recommended that the LCD be handled with soft gloves during assembly, etc. The polarizers on the LCD's surface are vulnerable to scratch and thus to be damaged by sharp particles.
- Do not drop water or any chemicals onto the LCD's surface.
- A protective film is supplied on the LCD and should be left in place until the LCD is required for operation.
- The ITO pad area needs special careful caution because it could be easily corroded. Do not contact the ITO pad area with HCFC, Soldering flux, Chlorine, Sulfur, saliva or fingerprint. To prevent the ITO corrosion, customers are recommended that the ITO area would be covered by UV or silicon.


深圳显昶光电科技有限公司		REV	ISSUE DATE	
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18	
GV101WXB-NN0-3GP0	XY101WXB-NN0Product Specification			PAGE 17 OF 23

8.3 Caution Against Static Charge

- The LCD modules use C-MOS LSI drivers, so customers are recommended that any unused input terminal would be connected to Vdd or Vss, do not input any signals before power is turn on, and ground you body, work/assembly area, assembly equipments to protect against static electricity.
- Remove the protective film slowly, keeping the removing direction approximate 30-degree not vertical from panel surface, If possible, under ESD control device like ion blower, and the humidity of working room should be kept over 50%RH to reduce the risk of static charge.
- Avoid the use work clothing made of synthetic fibers. We recommend cotton clothing or other conductivity-treated fibers.
- In handling the LCD, wear non-charged material gloves. And the conducting wrist to the earth and the conducting shoes to the earth are necessary.

8.4 Caution For operation

- It is indispensable to drive the LCD within the specified voltage limit since the higher Voltage than the limit causes the shorter LCD's life. An electro-chemical reaction due to DC causes undesirable deterioration of the LCD so that the use of DC drive should avoid.
- Do not connect or disconnect the LCD to or from the system when power is on.
- Never use the LCD under abnormal conditions of high temperature and high humidity.
- When expose to drastic fluctuation of temperature (hot to cold or cold to hot) ,the LCD may be affected; Specifically, drastic temperature fluctuation from cold to hot, produces dew on the LCD's surface which may affect the operation of the polarizer and the LCD.
- Response time will be extremely delayed at lower temperature than the operating temperature range and on the other hand at higher temperature LCD may turn black at temperature above its operational range. However those phenomena do not mean malfunction or out of order with the LCD. The LCD will revert to normal operation once the temperature returns to the recommended temperature range for normal operation.
- Do not display the fixed pattern for a long time because it may develop image sticking due to the LCD structure. If the screen is displayed with fixed pattern, use a screen saver.

深圳显昶光电科技有限公司		REV	ISSUE DATE	
Shenzhen Xianyang Optoelectronic Technology Co., Ltd		P0	2019-10-18	
GV101WXB-NN0-3GP0	XY101WXB-NN0Product Specification			PAGE 18 OF 23

8.5 Packaging

- Modules use LCD element, and must be treated as such.
 - Avoid intense shock and falls from a height.
 - To prevent modules from degradation, do not operate or store them exposed directly to sunshine or high temperature/humidity for long periods.

8.6 Storage

- A slight dew depositing on terminals is a cause for electro-chemical reaction resulting in terminal open circuit. Relative humidity of the environment should therefore be kept below 60%RH.
 - Original protective film should be used on LCD's surface (polarizer). Adhesive type protective film should be avoided, because it may change color and/or properties of the polarizers.
 - Do not store the LCD near organic solvents or corrosive gasses.
 - Keep the LCD safe from vibration, shock and pressure.
 - Black or white air-bubbles may be produced if the LCD is stored for long time in the lower temperature or mechanical shocks are applied onto the LCD.
 - In the case of storing for a long period of time for the purpose or replacement use, the following ways are recommended.
 - Store in a polyethylene bag with sealed so as not to enter fresh air outside in it.
 - Store in a dark place where neither exposure to direct sunlight nor light is.
 - Keep temperature in the specified storage temperature range.
 - Store with no touch on polarizer surface by anything else.
- If possible, store the LCD in the packaging situation LCD when it was delivered.


8.7 Safety


- For the crash damaged or unnecessary LCD, it is recommended to wash off liquid crystal by either of solvents such as acetone and ethanol and should be burned up later.
- In the case the LCD is broken, watch out whether liquid crystal leaks out or not. If your hands touch the liquid crystal, wash your hands cleanly with water and soap as soon as possible.
- If you should swallow the liquid crystal, first, wash your mouth thoroughly with water, then drink a lot of water and induce vomiting, and then, consult a physician.
- If the liquid crystal should get in your eyes, flush your eyes with running water for at least fifteen minutes.
- If the liquid crystal touches your skin or clothes, remove it and wash the affected part of your skin or clothes with soap and running water.

9.0 APPENDIX

Mechanical Drawing

Drawing Attachment: Front






Backlight LED Circuit


$I_f=120\text{mA}; V_f=18\text{V}$

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	REMARK
Center luminance	L_v	450	500		cd/m^2	中心点

Mechanical Drawing

Drawing Attachment:
Back





R2015-6014-A

