



电机极数	8
绝缘等级	F
防护等级	IP54
温控元件	PTC或KTY84
喷涂颜色	黑色哑光漆
编码器	1对极旋转变压器
编码器电压	7VDC
前轴承	6309/C3
后轴承	6306/C3
冷却风扇	单相220VAC电源

HC18系列电机技术参数

电机规格型号	额定转矩	额定功率	额定转速	额定电压	额定电流	额定频率	额定点反电势	电机重量	L	B
	N.m	kW	rpm	V	A	Hz	V			
HC18-40F10A	40	4.2	1000	380	8.4	66.6	325	47	450	170
HC18-40F15A	40	6.3	1500	380	12.6	100.0	325	47	450	170
HC18-40F17A	40	7.1	1700	380	14.2	113.3	325	47	450	170
HC18-40F20A	40	8.4	2000	380	16.8	133.3	325	47	450	170
HC18-62F10A	62	6.5	1000	380	13.0	66.6	325	50	450	170
HC18-62F15A	62	9.7	1500	380	19.5	100.0	325	50	450	170
HC18-62F17A	62	11.0	1700	380	22.1	113.3	325	50	450	170
HC18-62F20A	62	13.0	2000	380	26.0	133.3	325	50	450	170
HC18-70F10A	70	7.3	1000	380	14.7	66.6	325	53	485	205
HC18-70F15A	70	11.0	1500	380	22.0	100.0	325	53	485	205
HC18-70F17A	70	12.5	1700	380	24.9	113.3	325	53	485	205
HC18-70F20A	70	14.7	2000	380	29.3	133.3	325	53	485	205
HC18-88F10A	88	9.2	1000	380	18.4	66.6	325	56	485	205
HC18-88F15A	88	13.8	1500	380	27.6	100.0	325	56	485	205
HC18-88F17A	88	15.7	1700	380	31.3	113.3	325	56	485	205
HC18-88F20A	88	18.4	2000	380	36.9	133.3	325	56	485	205
HC18-105F10A	105	11.0	1000	380	22.0	66.6	325	64	520	240
HC18-105F15A	105	16.5	1500	380	33.0	100.0	325	64	520	240
HC18-105F17A	105	18.7	1700	380	37.4	113.3	325	64	520	240
HC18-105F20A	105	22.0	2000	380	44.0	133.3	325	64	520	240
HC18-128F10A	128	13.4	1000	380	26.8	66.6	325	71	555	275
HC18-128F15A	128	20.1	1500	380	40.2	100.0	325	71	555	275
HC18-128F17A	128	22.8	1700	380	45.6	113.3	325	71	555	275
HC18-128F20A	128	26.8	2000	380	53.6	133.3	325	71	555	275
HC18-148F10A	148	15.5	1000	380	31.0	66.6	325	77	590	310
HC18-148F15A	148	23.2	1500	380	46.5	100.0	325	77	590	310
HC18-148F17A	148	26.3	1700	380	52.7	113.3	325	77	590	310
HC18-148F20A	148	31.0	2000	380	62.0	133.3	325	77	590	310
HC18-168F10A	168	17.6	1000	380	35.2	66.6	325	85	625	345
HC18-168F15A	168	26.4	1500	380	52.8	100.0	325	85	625	345
HC18-168F17A	168	29.9	1700	380	59.8	113.3	325	85	625	345
HC18-168F20A	168	35.2	2000	380	70.4	133.3	325	85	625	345
HC18-176F10A	176	18.4	1000	380	36.9	66.6	325	91	660	380
HC18-176F15A	176	27.6	1500	380	55.3	100.0	325	91	660	380
HC18-176F17A	176	31.3	1700	380	62.7	113.3	325	91	660	380
HC18-176F20A	176	36.9	2000	380	73.7	133.3	325	91	660	380